

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**



(19)

(11) Publication number: **02098955 A**

Generated Document.

**PATENT ABSTRACTS OF JAPAN**(21) Application number: **63252321**(51) Intl. Cl.: **H01L 21/66 H01L 21/205 H01L 21/28**(22) Application date: **06.10.88**

(30) Priority:

(43) Date of application publication: **11.04.90**

(84) Designated contracting states:

(71) Applicant: **MITSUBISHI ELECTRIC CORP**(72) Inventor: **MOMOTAKE YASUHIRO  
MOCHIZUKI HIROSHI**




(74) Representative:

**(54) MANUFACTURE OF SEMICONDUCTOR DEVICE**

(57) Abstract:

**PURPOSE:** To obtain a film thickness of a desired selective growth film in an element formation region, to measure a film thickness highly accurately and to realize high reliability of a semiconductor device by a method wherein a measuring region is set on a flattened substrate and is formed to be a pattern identical to a part to be measured in the element formation region.

**CONSTITUTION:** In a dicing line region II, one part of a substrate 1 is opened so as to be exposed; a plane shape of a contact hole 11 used as a measuring region is made to be a size identical to a contact hole 6 which has been formed in a region I to be used as a semiconductor



device. Accordingly, the contact hole formed in the dicing line region II is formed on a that substrate 1; its structure is not complicated. As a result, when a film thickness is measured by using the region, an influence by a state in a difference in level can be avoided; in addition, in the case of visible light irradiation, an influence by a multiple reflection can be avoided; a film thickness of a selective growth film 7 in the contact hole 11 can be measured with high accuracy.

COPYRIGHT: (C)  
1990,JPO&Japio